



► Caixas Estancas com Entradas Marcadas (para uso de Bucins)

► Cajas Estancas con Entradas Marcadas (para uso de Prensaestopas)

► Cable Junction Enclosures with Pre-moulded Knock-outs (for to use Cable Glands)










► Boîtes de Derivation Etanches (pour Presse-etoupés)

-  -5° C  
+60° C
-  Material Termoplástico  
Material Termoplástico  
Thermoplastic Material  
Materiel Termoplastique
-  Aplicação por pressão  
Aplicación presión  
Pressure application  
Application a pression
-  3/4  
Parafuso 3/4 volta  
Tornillo 3/4 volta  
Twist-Lock Screws  
Vis 3/4 Tour
-  Cores  
Colores  
Colours  
Couleurs











## Serie 200 - PG



REF		Dim. (mm)	IP	IK	N°	°C	Ø	ØCAB.	
220-A		80X80X50	55	08	7	750°	PG16	11-14	10/100
222-A		100X100X55	65	09	6	750°	PG16	11-14	1/102
221-A		150X110X70	65	09	10	750°	PG16	11-14	1/51
223-A		175X110X66	65	09	10	750°	PG16	11-14	1/45
223-ATA		175110X83	65	09	10	750°	PG16	11-14	1/36
225-A		190X150X70	65	09	10	750°	2 PG29 + 8 PG21	14-25	1/29
225-ATA		190X150X83	65	09	10	750°	2 PG29 + 8 PG21	14-25	1/24
224-A		220X170X120	65	09	10	750°	2 PG29 + 8 PG21	14-25	1/14
226-A		220X170X105	65	09	10	750°	2 PG29 + 8 PG21	14-25	1/17

## Serie 200 - Metric.



REF		Dim. (mm)	IP	IK	N°	°C	Ø	ØCAB.	
220-AM		80X80X50	55	08	7	750°	M20	11-14	10/100
222-AM		100X100X55	65	08	6	750°	M20/M25	11-14	1/102
221-AM		150X110X70	65	08	10	750°	6 M20 + 4 M25	11-14	1/51
223-AM		175X110X66	65	08	10	750°	M20/M25	11-14	1/45
223-ATAM		175110X83	65	08	10	750°	6 M20 + 4 M25	11-14	1/36
225-AM		190X150X70	65	08	10	750°	6 M20 + 4 M25	14-25	1/29
225-ATAM		190X150X83	65	08	10	750°	6 M20 + 4 M25	14-25	1/24
224-AM		220X170X120	65	08	10	750°	M25	14-25	1/14
226-AM		220X170X105	65	08	10	750°	M25	14-25	1/17